

Lacava

Features

Lacava featuring Twin-Pressed Technology

- Warm, beautiful, and natural, Lacava emulates quarried slate—with pronounced clefts and hollows that give a layered and structured appearance.
- The Twin-Pressed process heightens the natural look: A second stamping thoroughly presses detailed gradations and nuances of color and texture into the body, creating unequalled slate-like realism.
- Designed for multi-environment use—ideal both outdoors and in—Lacava offers very low, easy maintenance and long-lasting appearance. It's many times more durable than slate, and the longevity means less impact on the environment.

Twin-Pressed technology is a double-pressing process that is used to emulate rustic or natural stone. The first pressing step forms the semi-compact slab, where layers of powder decoration are applied, after which a final pressing is performed. This technology provides limitless possibilities for creating glazed or unglazed porcelain tile during the pressing stage. This ensures perfect integration between pre-compacted base and subsequently applied decorative layers. The unfired slab can then be divided up using a cutting machine to obtain the required sizes without having to stop production. The entire process maximizes natural shading variations on the finished product.

Colors

200 Hay — saturated, spicy golden tones

300 Khaki — warm medium browns

500 Ginger — blending of gray browns with subtle green cast

600 Rust — russet red-browns



Color shown is 600 Rust

 **Shaw** Tile & Stone™
shawfloors.com

Lacava | *porcelain tile*

Colors



Color 200 Hay



Color 300 Khaki



Color 500 Ginger



Color 600 Rust

Mosaic *Available in all colors*



Color 500 Ginger

Rectangular Mosaic

Available in all colors



Color 200 Hay

Shaw Industries, Inc.
PO Drawer 2128, Mail Drop 02601
Dalton, GA 30722-2128
1-800-441-7429

 **Shaw** Tile & Stone™
shawfloors.com

Tile Sizes



Color 200 Hay



Color 300 Khaki



Color 500 Ginger



Color 600 Rust

Field Tile	Style
13" x 13"	CS21D
18" x 18"	CS22D
6.5" x 6.5"	CS23D

Trim	
3" x 13" Bullnose	CS27D

Accent	
13" x 13" Mosaic	CS24D
13" x 13" Rectangle Mosaic	CS25D

Technical	
Wear Rating Group	4
Break Strength	431
Water Absorption	<.5%
COF (Wet)	.75

**OSHA (Occupational Safety and Health Administration) has established a recognized industry standard of 0.5 (wet and dry) for slip-resistant surfaces. The Americans with Disabilities Act (ADA) recommends, but does not require, "a Static Coefficient of Friction of 0.60 for accessible routes and 0.80 for ramps." ADA does not specifically state that 0.60 is both a dry and a wet requirement. It is important to note that any tile or other hard surface flooring can become slippery when wet or improperly maintained. Unless specifically stated by Shaw Industries, Inc., the use of Shaw Industries, Inc. ceramic tile is not recommended for exterior horizontal surfaces.*

Approved Usage



Tile & Stone™

shawfloors.com