



Color shown on floor and wall is 200.

 **Shaw** Tile & Stone™  
shawfloors.com

**Baru** | ceramic tile



# Tile & Stone™

shawfloors.com  
Shaw Industries, Inc.  
PO Drawer 2128, Mail Drop 02601  
Dalton, GA 30722-2128  
1-800-441-7429

## Baru

### Features

For visitors to the Caribbean coast, Isla Baru is a paradise of pristine beaches and sparkling blue waters. A favorite tropical haven, it's a place where dreams come true.

The Baru collection can make a home the place of dreams, with all the flavor of a tropical escape. It's a ceramic collection of styles that offer great versatility. Three organic colors are time-proven to be among the most popular in tile—pale sandy beige, deeper medium beige, and fashionable brown. Subtle to moderate surface variation creates the right touch of visual interest.

Baru—for a cool, peaceful look that makes home a haven.

### Colors



200 Coastal Beige



201 Sea Oat Khaki



700 Mission Brown

### Trim Pieces — Listello & Mosaic



200 Coastal Beige



201 Sea Oat Khaki



700 Mission Brown



200 Coastal Beige



201 Sea Oat Khaki



700 Mission Brown

### Tile Sizes

Field Tile	Style
13" x 13"	CS01D
18" x 18"	CS02D
6.5" x 6.5"	CS35D
8" x 12" Wall Tile	CS32D
<b>Trim</b>	
3" x 13" Bullnose	CS03D
2" x 8" Wall Bullnose	CS33D
<b>Accent</b>	
2.5" x 8" Listello	CS34D
13" x 13" Mosaic	CS04D

### Technical

Wear Rating Group	3
Break Strength	250 lbs. (13") 360 lbs. (18")
Water Absorption	7%
COF (Wet)	.52

*This tile features random variations of shade and texture within each carton. To insure optimum appearance, it is imperative that tiles from various cartons be continually blended during installation. Placement of tiles should be decided on before beginning installation.*

\*OSHA (Occupational Safety and Health Administration) has established a recognized industry standard of 0.5 (wet and dry) for slip-resistant surfaces. The Americans with Disabilities Act (ADA) recommends, but does not require, "a Static Coefficient of Friction of 0.60 for accessible routes and 0.80 for ramps." ADA does not specifically state that 0.60 is both a dry and a wet requirement. It is important to note that any tile or other hard surface flooring can become slippery when wet or improperly maintained. Products installed in an exterior application must comply with applicable ANSI 108 series of the "American National Standard Specifications for the Installation of Ceramic Tile" and comply with TCA installation methods applicable to installation conditions.

### Approved Usage

