



Colors shown 220 Noce

 **Shaw** Tile & Stone™  
shawfloors.com

**Vicenza** | ceramic tile



## Vicenza

### Features

A white-body ceramic, Vicenza presents the sought-after visual of unfilled, honed travertine. Defined swaths of pale color look like naturally occurring strata, while the unfilled areas provide dark accents for an eye-catching, intriguing effect.

- Two sizes include the sophisticated large format that's been trending up in tile:
  - ✦ 23x23
  - ✦ 13x13
- Two colors are proven to be excellent sellers:
- Clarity Digital Imaging provides outstanding realism, a selling plus:
  - ✦ Digital imaging method creates crisp, realistic designs
  - ✦ Separate 4-color processes produce amazing color clarity
  - ✦ Very low repeat—up to 10 times more image variety yields extraordinary authenticity like that found in nature



### Colors



**150 Bianco**—creamy, grayed white with gray and cinnamon fil




**220 Noce**—shades of taupe with fill in tones of brown and chocolate

### Accents 2 x 2 Mosaic



**150 Bianco**—creamy, grayed white with gray and cinnamon fil



**220 Noce**—shades of taupe with fill in tones of brown and chocolate

### Tile Sizes

Field Tile	Style
23" x 23"	CS34K
13" x 13"	CS35K
Trim	
Bullnose	CS60K
Accent	
2x2 Mosaic	CS61K
Technical	
Wear Rating Group	3
Break Strength	400 lbs.
Water Absorption	> 4%
COF (Wet)	.48

*This tile features random variations of shade and texture within each carton. To insure optimum appearance, it is imperative that tiles from various cartons be continually blended during installation. Placement of tiles should be decided on before beginning installation.*

\*OSHA (Occupational Safety and Health Administration) has established a recognized industry standard of 0.5 (wet and dry) for slip-resistant surfaces. The Americans with Disabilities Act (ADA) recommends, but does not require, "a Static Coefficient of Friction of 0.60 for accessible routes and 0.80 for ramps." ADA does not specifically state that 0.60 is both a dry and a wet requirement. It is important to note that any tile or other hard surface flooring can become slippery when wet or improperly maintained. Products installed in an exterior application must comply with applicable ANSI 108 series of the "American National Standard Specifications for the Installation of Ceramic Tile" and comply with TCA installation methods applicable to installation conditions.

### Approved Usage

