









Features

In this assortment of smooth, solid hickory styles, we've left the natural wood characteristics—like knots and mineral streaks—and used a satin finish to accentuate the wood's inherent beauty.

The color line is phenomenal—ranging from the clearly natural to the dark and richly stained. The lightest color is light and translucent, creating a beautifully authentic visual that shows all the characteristics of the wood. The medium to darker stain colors hide some of the rustic qualities, looking more formal and elegant. These three colors are our most proven winners—the biggest sellers in our highest-end hickory products.

Lucky Day truly offers something for all tastes, casual or sophisticated.

Specifications

(21/4")SW477 (31/4")SW478 Style

Thickness	3/4" (19mm)
Species	Hickory
Texture	Smooth
Gloss Level	50%
Janka Hardness Rating	1926
Edge Description	Microbeveled
End Description	Square
Sq. ft. per carton	(<i>SW477</i>)25.00
	(SW478)27.00
Sq. ft. per pallet	(SW477)700.00
	(SW478)756.00

Cartons may contain random length planks



This Shaw hardwood is warranted that the face surface of this product will not peel off or wear through for 30 years from the date of purchase.

Scuf_{Resist}

This product features ScufResist™ PLATINUM - Shaw's extremely wear resistant UV cured polyurethane finish with Aluminum Oxide designed to help resist household scuffing on hardwood floors.



This hardwood is rated High color and character variation with distinguishable color variation within each box. It is *imperative* that hardwood planks from various cartons be continually blended during installation to insure optimum appearance.



This Shaw hardwood meets the GREENGUARD indoor air quality requirements and is GREENGUARD Certified.

Cradle to Cradle Certified™ Products Program. This product is Cradle to Cradle Certified™ Silver.



This Shaw product can be installed above or on ground level.



This Shaw product is Made in the U.S.A.

Trim Pieces when ordering please include color number

TMD78



SFR334 Flush Reducer



SCR34 Threshold / Carpet Reducer T-Molding

SES34 Flush Stairnose



OTR96 Quarter Round





Understanding Characteristics of Solid Hardwood Floors



Bottom of Board Defect



Filled Character



Unfilled Character



Wormholes

Grading for Lucky Day falls within Shaw's "Classic" or "CV3" visual category which means that the product can include moderate to high amounts of color variation. Additionally, sound natural variations of the forest product and manufacturing imperfections including but not limited to: bark pockets, broken edge/broken corner, indentation, splits, machining imperfections, worm holes filled and unfilled, torn grain, mineral streaks in unlimited amounts, knots, unfilled character up to 3/8 of an inch, stick stain, Missing or shy tongue up to ¼ normal size, sound rot,

water marks and bottom of the board defects that do not make the ware layer unsound are allowed in the grade. Some, all or none of the characteristics' will be represented in the sample or room scene so it will be up to the sales person to insure the dealers understand what they are ordering. Also, the Product may contain varying degrees of naturally occurring wood characteristics commonly found in the No. 2 Common and Better Grade characteristics based on NOFMA unfinished Official Flooring Grading Rules (Sept. '02).



Mineral & Stain

A wide range of variation in visual related attributes such

as texture, grain, color, mineral, and naturally occurring character is allowed in Lucky Day. Variations in grain can be expected in the form of the direction of wood fibers, as in straight, spiral and curly grain. The direction of the grain, as well as the amount of figuring in the wood affects the way wood accepts stains and finishes. There can be pronounced differentiations in color between spring wood and summer wood or heartwood and sapwood as well. All of these naturally occurring phenomenon will affect the way the wood accepts stains and finishes which can result in a wide range of variability in finished appearance.

The following are not permitted in the grade: Large broken knots, advanced rot, or large unsound defects greater than the 5% industry accepted cull rate.

Dealers, installers, and consumers must understand the naturally occurring variation within Lucky Day as no two planks are identical, no two boxes of finished product are identical, and no two production populations are identical. The production process is designed to yield what the forest provides, and consumers can expect clear populations or character populations or mixed character populations when choosing Lucky Day.

Installers must rely on job site planning, material observation, and craftsmanship to ensure a successful installation of Lucky Day. Installers must give careful consideration to naturally occurring characteristics as the installation is planned and the floor is dry racked. Further, installers should work out of at least six boxes at a time, and pre-planned dry racking should take into consideration the naturally occurring variation of the grade. Successful installation of Lucky Day relies on a complete understanding of the grade, and pride in craftsmanship.

It would be advantageous from a sales and support standpoint to ensure that customers are aware of these naturally occurring variations, especially if it is not evidenced well or at all in their representative sample. There is no means by which to order this product without this variation as it is simply indigenous to the grade.

