



Color shown is 200 Savanna

 **Shaw** Tile & Stone™
shawfloors.com

Serengeti | *ceramic tile*



Tile & Stone™

shawfloors.com
Shaw Industries, Inc.
PO Drawer 2128, Mail Drop 02601
Dalton, GA 30722-2128
1-800-441-7429


Serengeti

Features


- Many have called it a paradise. The region known as the Serengeti Plains has long been a haven for plant and animal. Now, a Serengeti ceramic floor can help create a human haven. It's a little bit of paradise at home—thanks to the cool, calming sleekness of ceramic tile.
- An excellent value, Serengeti is made in the USA and comes in three popular, versatile colors. It's available in 12" and 16", with bullnose trim and mosaics.

Colors

- 200 Savanna
- 300 Meadow
- 700 Desert



200 Savanna



300 Meadow



700 Desert

Tile Sizes

Field Tile	Style
12" x 12"	CS28D
16" x 16"	CS29D
Trim	
3" x 12" Bullnose	CS30D
Accent	
12" x 12" Mosaic	CS31D
Technical	
Wear Rating Group	4
Break Strength	451 lbs. (16") 352 lbs. (12")
Water Absorption	3%
COF (Wet)	.60

This tile features moderate variations of shade and texture within each carton. To insure optimum appearance, it is imperative that tiles from various cartons be continually blended during installation. Placement of tiles should be decided on before beginning installation.

*OSHA (Occupational Safety and Health Administration) has established a recognized industry standard of 0.5 (wet and dry) for slip-resistant surfaces. The Americans with Disabilities Act (ADA) recommends, but does not require, "a Static Coefficient of Friction of 0.60 for accessible routes and 0.80 for ramps." ADA does not specifically state that 0.60 is both a dry and a wet requirement. It is important to note that any tile or other hard surface flooring can become slippery when wet or improperly maintained. Products installed in an exterior application must comply with applicable ANSI 108 series of the "American National Standard Specifications for the Installation of Ceramic Tile" and comply with TCA installation methods applicable to installation conditions.

Approved Usage

