

## **PEBBLE HILL HICKORY**

engineered



144 Prairie Dust



304 Burnt Barnboard



510 Stonehenge



885 Olde English



941 Weathered Saddle

shawfloors.com direct 08.02.18 HS-308189-18





## PEBBLE HILL HICKORY



Style Number	SW219
Construction	Epic Plus
Thickness	3/8" (8.2mm)
Width	5″
Species	Hickory
Texture	Scraped
Gloss Level	20%
Edge Description	Microbeveled
End Description	Microbeveled
SF per carton	23.66
SF per pallet	1,419.60
Installation	Nail, Staple, Glue, Float
Installation Grade	Above, On, Below
Color Variation	High
Radiant Heat Approved	Yes
GREENGUARD Certified	Yes
Warranty	Lifetime
All massurements are nominal. Cartans may include random lengths	

All measurements are nominal. Cartons may include random lengths

## **Sundry Recommendations**

Style #	Style Name	Coverage	Moisture Test	Additional Features	
ADHESIVES					
HS105	35MC — Urethane	35 SF / gal for moisture	No moisture test required	Sound control & crack suppressant	
		60 SF / gal as adhesive	Up to 5 lbs. or 85% RH		
111SA	3-in-1 Ultra — MS	35 SF / gal for moisture	No moisture test required	Sound control & crack suppressant	
		70 SF / gal as adhesive	Up to 5 lbs. or 85% RH		
SWADH	UreBond Plus	35 SF / gal for moisture	Up to 8 lbs. or 85% RH		
		60 SF / gal	Up to 5 lbs. or 85% RH		

**Trim Pieces** – Length: 78" (\*Overlap Reducer and Overlap Stairnose are designed for floating installations only. These items are non-stocking – but are available through a quick-ship program. Delivery should take approximately 2 to 3 weeks.)





MADE IN THE USA

