



Color shown on floor is 100 Beige and 200 Sabbia with border in color 100 Multi

 **Shaw** Tile & Stone™
shawfloors.com

Pantheon | *porcelain tile*



Tile & Stone™

shawfloors.com

Shaw Industries, Inc.

PO Drawer 2128, Mail Drop 02601

Dalton, GA 30722-2128

1-800-441-7429

Pantheon

Features

- This stunning porcelain tile features a natural travertine look with uniquely sculpted edges resembling tumbled stone
- Rustic appearance
- Superior stain and fade resistance
- Natural, blended colorations
- Frost resistant for interior and covered exterior

Tile Sizes

Field Tile	Style
13" x 13"	CS816
20" x 20"	CS817
Trim	
3" x 13" Bullnose	CS818
Accent	
4" x 13" Border	CS841
Technical	
Wear Rating Group	5 and 4*
Break Strength	385 lbs.
Water Absorption	.5%
COF (Wet)	.58

Colors



100 Beige



200 Sabbia



600 Prova



700 Noce

*Wear rating 5, colors 100 and 200
Wear rating 4, colors 600 and 700

This tile features random variations of shade and texture within each carton. To insure optimum appearance, it is imperative that tiles from various cartons be continually blended during installation. Placement of tiles should be decided on before beginning installation.

Accents



Border

*OSHA (Occupational Safety and Health Administration) has established a recognized industry standard of 0.5 (wet and dry) for slip-resistant surfaces. The Americans with Disabilities Act (ADA) recommends, but does not require, "a Static Coefficient of Friction of 0.60 for accessible routes and 0.80 for ramps." ADA does not specifically state that 0.60 is both a dry and a wet requirement. It is important to note that any tile or other hard surface flooring can become slippery when wet or improperly maintained. Products installed in an exterior application must comply with applicable ANSI 108 series of the "American National Standard Specifications for the Installation of Ceramic Tile" and comply with TCA installation methods applicable to installation conditions.

Approved Usage

