

938 Coffee Bean

SPOKANE



Style Number	HW119	HW120
Construction	Stabilitek Core	Stabilitek Core
Thickness	3/8"	3/8"
Width	3/4"	5"
Species	Red Oak	Red Oak
Texture	Smooth	Smooth
Gloss Level	40%	40%
Janka Hardness Rating	1802	1802
Edge Description	Microbeveled	Microbeveled
End Description	Microbeveled	Microbeveled
SF per carton	19.80	19.72
SF per pallet	1,188.00	1,183.20
Installation	Nail, Staple, Glue, Float	Nail, Staple, Glue, Float

Cartons may include random lengths

Features

- Classic oak flooring in a smooth full-filled finish
- Color palette offers seven traditional shades
- Available in two widths - 3/4" and 5"


Sundry Recommendations

Style #	Style Name	Coverage	Moisture Test	Additional Features
ADHESIVES				
HWA05	35MC – Urethane	35 SF / gal for moisture	No Moisture test required	Sound control & crack suppressant
		60 SF / gal as adhesive	Up to 5 lbs. or 85% RH	
111BA	3-in-1 Ultra – MS	35 SF / gal for moisture	No Moisture test required	Sound control & crack suppressant
		70 SF / gal as adhesive	Up to 5 lbs. or 85% RH	
HS303	DMC140 – Urethane	35 SF / gal for moisture	No Moisture test required	
HWADH	UreBond Plus	35 SF / gal for moisture	Up to 8 lbs. or 85% RH	
		60 SF / gal	Up to 5 lbs. or 85% RH	

Trim Pieces length: 78" (*Overlap Reducer and Overlap Stairnose are designed for floating installations only. These items are non-stocking – but are available through a quick-ship program. Deliver should take approximately 2 to 3 weeks.)



HW829
Flush Reducer



HW833
*Overlap Reducer



HW831
Flush Stairnose



HW835
*Overlap Stairnose



HW838
Threshold | Carpet Reducer



HW839
T-Molding



HW836
Quarter Round

Benefits

