



Color shown is I00 Latte with CS26A Autumn Slate listello color 200 and CS25A Autumn Slate 4" x 4" inserts.

 **Shaw** Tile & Stone™
shawfloors.com

African Slate | *porcelain tile*



Tile & Stone™

shawfloors.com

Shaw Industries, Inc.

PO Drawer 2128, Mail Drop 02601

Dalton, GA 30722-2128

1-800-441-7429

African Slate

Features

- Intriguing variations in color give this stunning glazed porcelain tile an intricate surface texture reminiscent of natural riverbed slate
- Porcelain construction
- Frost resistant for interior and covered exterior floor tile applications only
- Three colors available in 13" and 18" field tiles

Tile Sizes

Field Tile	Style
13" x 13"	CS65A
18" x 18"	CS66A

Trim	
3" x 13" Bullnose	CS67A

Technical	
Wear Rating Group	3
Break Strength	390 lbs.
Water Absorption	<.5%
COF (Wet)	.40

Colors



100 Latte



200 Sand



600 Rust

This tile features random variations of shade and texture within each carton. To insure optimum appearance, it is imperative that tiles from various cartons be continually blended during installation. Placement of tiles should be decided on before beginning installation.

*OSHA (Occupational Safety and Health Administration) has established a recognized industry standard of 0.5 (wet and dry) for slip-resistant surfaces. The Americans with Disabilities Act (ADA) recommends, but does not require, "a Static Coefficient of Friction of 0.60 for accessible routes and 0.80 for ramps." ADA does not specifically state that 0.60 is both a dry and a wet requirement. It is important to note that any tile or other hard surface flooring can become slippery when wet or improperly maintained. Products installed in an exterior application must comply with applicable ANSI 108 series of the "American National Standard Specifications for the Installation of Ceramic Tile" and comply with TCA installation methods applicable to installation conditions.

Approved Usage

