



306 Bayou Brown



881 Burnt Sugar

ALBERMARLE HICKORY



Style Number	SA000
Construction	Epic Plus
Thickness	3/8" (8.2mm)
Width	5"
Species	Hickory
Texture	Distressed
Gloss Level	20%
Janka Hardness Rating	2584
Edge Description	Microbeveled
End Description	Microbeveled
SF per carton	23.66
SF per pallet	1,419.60
Installation	Nail, Staple, Glue, Float
All measurements are nominal	Cartons may include random lengths

Features

- Blackened distressing and dramatic texturing showcase the rich hickory wood grain
- Pronounced variation in color and distressing from one plank to the next

Sundry Recommendations

Style #	Style Name	Coverage	Moisture Test	Additional Features
ADHESIVES				
HS105	35MC – Urethane	35 SF / gal for moisture	No Moisture test required	Sound control & crack suppressant
		60 SF / gal as adhesive	Up to 5 lbs. or 85% RH	
111SA	3-in-1 Ultra – MS	35 SF / gal for moisture	No Moisture test required	Sound control & crack suppressant
		70 SF / gal as adhesive	Up to 5 lbs. or 85% RH	
HS304	DMC140 – Urethane	35 SF / gal for moisture	No Moisture test required	
SWADH	UreBond Plus	35 SF / gal for moisture	Up to 8 lbs. or 85% RH	
		60 SF / gal	Up to 5 lbs. or 85% RH	

Trim Pieces length: 78" (*Overlap Reducer and Overlap Stairnose are designed for floating installations only. These items are non-stocking – but are available through a quick-ship program. Delivery should take approximately 2 to 3 weeks.)



Benefits

