









Specifications

HW540 31/4"	HW541 5"
(9.5mm)	3/8" (9.5mm)
Red Oak	Red Oak
Smooth	Smooth
20%	20%
1889	1889
beveled	Microbeveled
beveled	Microbeveled
19.80	19.72
1,188.00	1,183.20
	(9.5mm) Red Oak Smooth 20% 1889 beveled beveled

Cartons may contain random length planks

Features

All In showcases seven distinct oak colors with naturally random variation providing a distinct visual range — from planks with extreme character, graining and color variation to those with a clean and consistent look... and everything in between. Extreme variation should be expected.

Style	Adhesive	Coverage	Moisture Control	Other
HWADH	UreBond Plus	60 sq. ft./gal	Up to 5 lbs or 85% RH	Most popular
HWA05	35MC	60 sq. ft./gal as adhesive	Up to 5 lbs or 85% RH	Sound control & crack suppressant
		35 sq. ft./gal for moisture	Yes, no limit	
HS303	DMC 140	35 sq. ft./gal for moisture	Yes, no limit	

^{*}We recommend that you use Shaw's adhesives to prolong the life, durability and performance of your beautiful new EPIC Plus hardwood floor.



This Shaw Duras hardwood is warranted that the finish will not peel off or wear through for 50 years.



This Shaw hardwood is approved for installation over water type radiant heated subfloors. Floating installation method only. Direct glue-down is NOT recommended!



This product features ScufResist™ PLATINUM - Shaw's extremely wear resistant UV cured polyurethane finish with Aluminum Oxide designed to help resist household scuffing on hardwood floors.



This hardwood is rated High color and character variation with distinguishable color variation within each box. It is imperative that hardwood planks from various cartons be continually blended during installation to insure optimum appearance.



This Shaw hardwood meets the GREENGUARD indoor air quality requirements and is GREENGUARD Certified.



This Shaw hardwood is Cradle to Cradle^{CM} Silver Certified.



This Shaw product can be installed above, on or below ground level.



Made in the U.S.A.

Trim Pieces when ordering please include color number



Reducer





Reducer





HSO38 Overlap Stairnose



HCR38 Threshold / Carpet Reducer



HWTMD T-Molding



HWQR0 Quarter Round