



Colors shown 700 Bruno

**Shaw** Tile & Stone™  
shawfloors.com

**Augustino** | *porcelain tile*

CERTIFIED  
**PORCELAIN**™  
TILE  
0.5% or less water absorption

## Augustino

### Features

- A sophisticated glazed porcelain, Augustino reveals hints of metamorphic stones creating an exciting, organic linear stone visual. The smooth surface coupled with hues of grey and taupe, adds a quiet elegance to this versatile porcelain.

### Colors



200 Bianco



220 Siena



700 Bruno

### Accents

#### 2 x 2 Mosaic



200 Bianco



220 Siena




700 Bruno

#### Random Linear Mosaic



200 Bianco



220 Siena



700 Bruno

### Tile Sizes

Field Tile	Style
6x6	CS09H
12x12	CS08H
20x20	CS07H
Trim	
Bullnose	CS10H
Accent	
2x2 Mosaic	CS11H
Random Linear Mosaic	CS57J
Technical	
Wear Rating Group	3*
Break Strength	350 lbs.
Water Absorption	< .5%
COF (Wet)	.45

*This tile features random variations of shade and texture within each carton. To insure optimum appearance, it is imperative that tiles from various cartons be continually blended during installation. Placement of tiles should be decided on before beginning installation.*

\*OSHA (Occupational Safety and Health Administration) has established a recognized industry standard of 0.5 (wet and dry) for slip-resistant surfaces. The Americans with Disabilities Act (ADA) recommends, but does not require, "a Static Coefficient of Friction of 0.60 for accessible routes and 0.80 for ramps." ADA does not specifically state that 0.60 is both a dry and a wet requirement. It is important to note that any tile or other hard surface flooring can become slippery when wet or improperly maintained. Products installed in an exterior application must comply with applicable ANSI 108 series of the "American National Standard Specifications for the Installation of Ceramic Tile" and comply with TCA installation methods applicable to installation conditions.



### Approved Usage

