



700 Cafe

Style Number	CS09F	CS10F	CS79L	CS43J	CS12F	CS80L	CS14F
<b>Construction</b>	ceramic	ceramic	ceramic	ceramic	ceramic	ceramic	ceramic
<b>Tile Type</b>	floor tile	floor tile	wall tile	floor tile	bullnose	wall bullnose	wall listello
<b>Tile Size</b>	13"x13"	17"x17"	10"x16"	6.5"x6.5"	2.75"x13"	2"x10"	4"x8"

## Technical

<b>Wear Rating Group</b>	4	4	4	4	4	4	4
<b>Break Strength</b>	412 lbs.	412 lbs.	304 lbs.	412 lbs.	412 lbs.	304 lbs.	304 lbs.
<b>Water Absorption</b>	6%	6%	6%	6%	6%	6%	6%
<b>DCOF</b>	> 0.42	> 0.42	> 0.42	> 0.42	> 0.42	> 0.42	> 0.42
<b>Shade Variation</b>	V2	V2	V2	V2	V2	V2	V2

A DCOF value of > 0.42 is the new standard for tiles specified for commercial application in standard A137.1-2012, Section 9.6. It replaces the SCOF value of > 0.60 referenced in ASTM C1028. For more information on the correlation between the two values and about the DCOF AcuTest visit the Tile Council of North America's website: [www.tcnatile.com](http://www.tcnatile.com)

### MANUFACTURER'S WARNING:

- Tiles with DCOF Acutest values less than .42 are not recommended for use in areas with wet or slippery conditions. If such tiles are used as a walking surface where water, ice, oil, great and/or other substances are present, such a condition could cause a reduction in foot traction and become unexpectedly slippery resulting in a fall and personal injury. See ANSI standard A137.1 section 6.2.2.1.10, available at [www.tcnatile.com/sections6.2.2.1.10.html](http://www.tcnatile.com/sections6.2.2.1.10.html).

- Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.

- For additional information, refer to [Factors to Consider](#).

- Since there is a shade variation on all natural products, the tile and trim supplied for your particular installation may not match these samples. Final selection should be made from actual tiles and trim and not from tile and trim samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

## Colors



100 Bone



200 Beige



700 Cafe

### 4" x 8" Mosaic CS14F



101 Multi

## Benefits

