



Color shown 101 Multi Mosaic on walls, with 200 Beige on the floors.

 **Shaw** Tile & Stone™
shawfloors.com

Padova | porcelain tile

Padova

Features

With today's endless options and confusing designs available in market — once in a while a simple product comes along that makes designing a room with a custom feel as easy as 1, 2, 3.

Padova's coordinated floor & wall tile, accents, and trim options, along with an intriguing neutral color pallet that flawlessly incorporates beiges, browns and greys into 4 color lines, makes this product the go to porcelain for kitchens, baths, and any other living space. Each color has been meticulously blended to coordinate with today's cabinetry stains and hottest paint colors, accentuated by coordinated wall tile with resin decos, listellos and chair rails. For those looking for an added pizzazz, multi color decors are available in a floor border with shimmering metal accents, wall listello — easily set off using the chair rail as a frame — and finally a blended 2" x 4" mosaic.

So go ahead, let your imagination and confidence in designing the perfect room run wild!

- Floor & Wall combination
- Made in Brazil
- PTCA Certified Porcelain

Tile Sizes

Field Tile	Style
12x12	CS04G
18x18	CS05G
10x13 Wall*	CS06G

Trim

Bullnose	CS08G
Wall Bullnose	CS09G
Resin Chair Rail	CS13G

Accent

Wall Deco - Resin Insert*	CS07G
Resin Listello	CS12G
Border	CS10G
Diamond Wall Listello*	CS11G

Technical

Wear Rating Group	4 and 3**
Break Strength	250 lbs.
Water Absorption	< .5%
COF (Wet)	.55

*Ceramic Body

**Wear rating 3, color 700

This tile features random variations of shade and texture within each carton. To insure optimum appearance, it is imperative that tiles from various cartons be continually blended during installation. Placement of tiles should be decided on before beginning installation.

*OSHA (Occupational Safety and Health Administration) has established a recognized industry standard of 0.5 (wet and dry) for slip-resistant surfaces. The Americans with Disabilities Act (ADA) recommends, but does not require, "a Static Coefficient of Friction of 0.60 for accessible routes and 0.80 for ramps." ADA does not specifically state that 0.60 is both a dry and a wet requirement. It is important to note that any tile or other hard surface flooring can become slippery when wet or improperly maintained. Products installed in an exterior application must comply with applicable ANSI 108 series of the "American National Standard Specifications for the Installation of Ceramic Tile" and comply with TCA installation methods applicable to installation conditions.



Approved Usage



Colors



100 Blanco

200 Beige

500 Gray

700 Brown

Accents & Trims

Available In All Colors



Subway Mosaic 200



Wall Tile 200



Wall Deco 200

101 Multicolor Trims

Coordinate With All Colors



Subway Mosaic



Bullnose 200



Chair Rail 200



Wall Bullnose 200



Wall Listello 200



Floor Border



Wall Listello