



Color shown on floor is 200 and 600 with deco border

 **Shaw** Tile & Stone™
shawfloors.com

Baja | porcelain tile



Tile & Stone™

shawfloors.com

Shaw Industries, Inc.

PO Drawer 2128, Mail Drop 02601

Dalton, GA 30722-2128

1-800-441-7429

Baja

Features

- Variations in color and texture are blended to produce an authentic slate visual that will accent your home's decor
- Porcelain construction
- Frost resistant for interior and covered exterior

Colors



100



200



300




400



600

Accents



Deco Border

Tile Sizes

Field Tile	Style
13" x 13"	CS277
18" x 18"	CS257
6.5" x 6.5"	CS278

Trim

3" x 13" Bullnose	CS279
Quarter Round	CS353
Quarter Round Beak	CS354
V-Cap	CS280
V-Cap Corner	CS281

Accent

4" x 13" Deco Border	CS282
----------------------	-------

Technical

Wear Rating Group	5
Break Strength	321 lbs.
Water Absorption	.5%
COF (Wet)	.65

This tile features random variations of shade and texture within each carton. To insure optimum appearance, it is imperative that tiles from various cartons be continually blended during installation. Placement of tiles should be decided on before beginning installation.

*OSHA (Occupational Safety and Health Administration) has established a recognized industry standard of 0.5 (wet and dry) for slip-resistant surfaces. The Americans with Disabilities Act (ADA) recommends, but does not require, "a Static Coefficient of Friction of 0.60 for accessible routes and 0.80 for ramps." ADA does not specifically state that 0.60 is both a dry and a wet requirement. It is important to note that any tile or other hard surface flooring can become slippery when wet or improperly maintained. Products installed in an exterior application must comply with applicable ANSI 108 series of the "American National Standard Specifications for the Installation of Ceramic Tile" and comply with TCA installation methods applicable to installation conditions.

Approved Usage

