



Shaw
Tile & Stone™

Crosscut | ceramic tile

Colors shown 700 Noce

shawfloors.com





Tile & Stone™

shawfloors.com

Shaw Industries, Inc.
PO Drawer 2128, Mail Drop 02601
Dalton, GA 30722-2128
1-800-441-7429

Crosscut

Features

Resembling a stunning cross-cut travertine, this white-body ceramic truly makes a statement. It has a larger fill, a rather rustic, mossy character, and high color movement—with many shades of the same color within the same tile. Add the large format that's been coming on strong lately, and you have a decidedly high-end look.

- 23X23 and 13X13
- Slip- resistant
- Clarity Digital Imaging
 - ✦ Digital imaging method creates crisp, realistic designs
 - ✦ Separate 4-color processes produce amazing color clarity
 - ✦ Very low repeat—up to 10 times more image variety yields extraordinary authenticity like that found in nature



Colors



100 Blanco —field of creamy color with tones in pale taupe, dove gray, and sand



200 Musgo — swirls in pale coffee tones with cream and taupe-grey



700 Noce — light to medium golden caramels in the background, with veins in darker earth tones

Accents 2 x 2 Mosaic



100 Blanco —field of creamy color with tones in pale taupe, dove gray, and sand



200 Musgo — swirls in pale coffee tones with cream and taupe-grey



700 Noce — light to medium golden caramels in the background, with veins in darker earth tones

Tile Sizes

Field Tile	Style
23" x 23"	CS32K
13" x 13"	CS33K

Trim

Bullnose	CS58K
----------	-------

Accent

2x2 Mosaic	CS59K
------------	-------

Technical

Wear Rating Group	4*
Break Strength	400 lbs.
Water Absorption	> 4%
COF (Wet)	.72

This tile features random variations of shade and texture within each carton. To insure optimum appearance, it is imperative that tiles from various cartons be continually blended during installation. Placement of tiles should be decided on before beginning installation.

*OSHA (Occupational Safety and Health Administration) has established a recognized industry standard of 0.5 (wet and dry) for slip-resistant surfaces. The Americans with Disabilities Act (ADA) recommends, but does not require, "a Static Coefficient of Friction of 0.60 for accessible routes and 0.80 for ramps." ADA does not specifically state that 0.60 is both a dry and a wet requirement. It is important to note that any tile or other hard surface flooring can become slippery when wet or improperly maintained. Products installed in an exterior application must comply with applicable ANSI 108 series of the "American National Standard Specifications for the Installation of Ceramic Tile" and comply with TCA installation methods applicable to installation conditions.

Approved Usage

