



Color shown 200 Sand

Shaw Tile & Stone™
shawfloors.com

RidgeStone | *porcelain tile*

Green.
It's something we never forget.™



RidgeStone

Features

A Classic and timeless stone, RidgeStone emulates quartzite flawlessly. Raw and irregular in appearance with a very matte surface and high variation, the patterns and colors take on a life of their own, creating not only a realistic visual but realistic feeling. Using Clarity Digital Imaging™, RidgeStone is the perfect product for indoor and outdoor living areas — offering subtle and softly colored neutrals, visually ranging from tight and compact to loose and flowing grains — speckled to velvety. Full body construction adds to the realistic visual and offers peace of mind in durability and maintenance.

- Clarity Digital Imaging™ creates the most realistic look with a dimensional feel and dozens of unique patterns.
- RidgeStone has an earthy appearance with subtle and softly colored neutrals.
- Sandy and undulated texture—ideal for non-slip surfaces
- PTCA Certified Porcelain
- Full Body Porcelain—color goes all the way through adding to the realism and durability
- 10% recycled content
- Made in the USA

Tile Sizes

Field Tile	Style
12x12	CS43F
18x18	CS44F
12x24	CS46F
6X6	CS29G

Trim

Bullnose	CS47F
Cove Base	CS51F
Inside Corner	CS52F
Outside Corner	CS53F

Accent

Border	CS50F
Mosaic	CS45F

Technical

Wear Rating Group	4
Break Strength	454 lbs.
Water Absorption	< .5%
COF (Wet)	.6

This tile features random variations of shade and texture within each carton. To insure optimum appearance, it is imperative that tiles from various cartons be continually blended during installation. Placement of tiles should be decided on before beginning installation.

*OSHA (Occupational Safety and Health Administration) has established a recognized industry standard of 0.5 (wet and dry) for slip-resistant surfaces. The Americans with Disabilities Act (ADA) recommends, but does not require, "a Static Coefficient of Friction of 0.60 for accessible routes and 0.80 for ramps." ADA does not specifically state that 0.60 is both a dry and a wet requirement. It is important to note that any tile or other hard surface flooring can become slippery when wet or improperly maintained. Products installed in an exterior application must comply with applicable ANSI 108 series of the "American National Standard Specifications for the Installation of Ceramic Tile" and comply with TCA installation methods applicable to installation conditions.



Approved Usage



Colors



200 Sand

500 Silver

600 Beige

Accents

MOSAIC



200 Sand

500 Silver

600 Beige

BORDER



Trim



Bullnose



Cove Base



Inside Corner



Outside Corner

