



Color shown 300 Luna Park

Shaw Tile & Stone™
shawfloors.com

Metropolitan Slate | *porcelain tile*

GREEN. It's something we never forget.®



Tile & Stone™

shawfloors.com

Shaw Industries, Inc.
PO Drawer 2128, Mail Drop 02601
Dalton, GA 30722-2128
1-800-441-7429

Metropolitan Slate

Features

Explosive colors and ultra realism, coupled with low maintenance of porcelain tile, highlight the many features of Metropolitan Slate. Made in the USA of 40% recycled materials, Metropolitan Slate also features Shaw's Clarity Digital Imaging™ technology allowing for up to 10 times more unique patterns before repeating compared to traditional glazing techniques. From the rustic multi-colored "Urban Jungle", to the sophisticated cleanliness of "Silver Lake", Metropolitan Slate offers colors and styles fitting for the Denver Retreat to the South Beach Loft.

- The stunning look of slate without the maintenance and upkeep issues. No sealing, no flaking, and no yearly upkeep.
- Clarity Digital Imaging™ creates the most realistic look with a dimensional feel and dozens of unique patterns.
- Made in the USA
- 40% recycled content
- PTCA Certified Porcelain

Colors



100 Silver Lake



200 Tribeca



300 Luna Park



900 Urban Jungle

Accents

MOSAICS



100 Silver Lake



200 Tribeca



300 Luna Park



900 Urban Jungle

SUBWAY MOSAICS



100 Silver Lake



200 Tribeca



300 Luna Park



900 Urban Jungle

Tile Sizes

Field Tile	Style
12x12	CS54F
18x18	CS55F
12x24	CS56F
6X6	CS30G

Trim

Bullnose	CS63F
Cove Base	CS65F
Inside Corner	CS66F
Outside Corner	CS67F

Accent

Mosaic	CS64F
--------	-------

Technical

Wear Rating Group	4 & 3*
Break Strength	>400 lbs.
Water Absorption	< .5%
COF (Wet)	.6

*Wear rating 3, color 900

This tile features random variations of shade and texture within each carton. To insure optimum appearance, it is imperative that tiles from various cartons be continually blended during installation. Placement of tiles should be decided on before beginning installation.

*OSHA (Occupational Safety and Health Administration) has established a recognized industry standard of 0.5 (wet and dry) for slip-resistant surfaces. The Americans with Disabilities Act (ADA) recommends, but does not require, "a Static Coefficient of Friction of 0.60 for accessible routes and 0.80 for ramps." ADA does not specifically state that 0.60 is both a dry and a wet requirement. It is important to note that any tile or other hard surface flooring can become slippery when wet or improperly maintained. Products installed in an exterior application must comply with applicable ANSI 108 series of the "American National Standard Specifications for the Installation of Ceramic Tile" and comply with TCA installation methods applicable to installation conditions.



Approved Usage



Metropolitan Slate | porcelain tile

GREEN. It's something we never forget.®