



Product shown is color 700 Nova Roca in 18" floor tile and coordinating mosaic installed on fireplace.

 **Shaw** Tile & Stone™
shawfloors.com

Saturnia | *porcelain tile*

Tile & Stone™

Saturnia

Features

- A beautifully colored porcelain tile that's all about affordable luxury—fashion forward styling at an ultra-competitive price point.
- As trends move away from travertine, this is the hot look of limestone with light, marbled veining and tonal motion—a look usually found only in high-end products.
- Creates a floor rich in texture and movement, with an earthy quarried look.
- Coordinates handsomely with Philadelphia's Game Changer carpet.

Colors

Golden Beach 200—a mid-tone sandy beige

Platina 500—smoky gray (an up-and-coming color) with a subtle blue cast

Nova Roca 700—milk chocolate shading into cocoas and grays



Color 200 Golden Beach



Color 500 Platina



Color 700 Nova Roca

Mosaic



Tile Sizes

Field Tile	Style
13" x 13"	CS58C
18" x 18"	CS59C

Trim	Style
3" x 13" Bullnose	CS66C

Accent	Style
13" x 13" Mosaic	CS75C

Technical	
Wear Rating Group	3
Break Strength	390 lbs.
Water Absorption	.5%
COF (Wet)	.58

This tile features random variations of shade and texture within each carton. To insure optimum appearance, it is imperative that tiles from various cartons be continually blended during installation. Placement of tiles should be decided on before beginning installation.

*OSHA (Occupational Safety and Health Administration) has established a recognized industry standard of 0.5 (wet and dry) for slip-resistant surfaces. The Americans with Disabilities Act (ADA) recommends, but does not require, "a Static Coefficient of Friction of 0.60 for accessible routes and 0.80 for ramps." ADA does not specifically state that 0.60 is both a dry and a wet requirement. It is important to note that any tile or other hard surface flooring can become slippery when wet or improperly maintained. Products installed in an exterior application must comply with applicable ANSI 108 series of the "American National Standard Specifications for the Installation of Ceramic Tile" and comply with TCA installation methods applicable to installation conditions.

Approved Usage

