



CERTIFIED
PORCELAIN
TILE
0.5% or less water absorption

 **Shaw** Tile & Stone™

Lunar | *porcelain tile*

Color shown is 701 Noce

 Sustainability Through Innovation™

That's the **Shaw Green Edge**®

shawfloors.com

Lunar

Features

- Designed in Italy and made in the USA, Lunar is a line unique to Shaw
- This tile collection, a dramatic design, is inspired by images of the moon's surface
- Randomness is achieved by advanced technology and numerous glazing steps—for a look that's very natural
- Four colors, each with light to dark movement across the tile, echo the natural palette of stone
- This product was manufactured with conscientious environmental practices in mind and contains 40% post-industrial recycled content
- Modular design series in 12" x 12", 18" x 18", 6" x 6", and 3" x 6" tiles with 2" x 2" mosaics



Tile Sizes

Field Tile	Style
12" x 12"	CS60C
18" x 18"	CS61C
6" x 6"	CS62C
3" x 6"	CS93C

Trim	
3" x 12" Bullnose	CS63C

Accent	
12" x 12" Mosaic	CS64C

Technical	
Wear Rating Group	4
Break Strength	400 lbs.
Water Absorption	<.5%
COF (Wet)	.60

This tile features random variations of shade and texture within each carton. To insure optimum appearance, it is imperative that tiles from various cartons be continually blended during installation. Placement of tiles should be decided on before beginning installation.

*OSHA (Occupational Safety and Health Administration) has established a recognized industry standard of 0.5 (wet and dry) for slip-resistant surfaces. The Americans with Disabilities Act (ADA) recommends, but does not require, "a Static Coefficient of Friction of 0.60 for accessible routes and 0.80 for ramps." ADA does not specifically state that 0.60 is both a dry and a wet requirement. It is important to note that any tile or other hard surface flooring can become slippery when wet or improperly maintained. Products installed in an exterior application must comply with applicable ANSI 108 series of the "American National Standard Specifications for the Installation of Ceramic Tile" and comply with TCA installation methods applicable to installation conditions.

Colors



200 Beige



700 Walnut



701 Noce



702 Graphite

Accents

Mosaic




200 Beige



700 Walnut



701 Noce



702 Graphite



Approved Usage

