

Color shown 500 Relic





Tile & Stone™

Features

You've requested it, and here it is: a wood-look porcelain tile! And Petrified Hickory offers so much, you'll be amazed:

- Highly desirable wood plank look—glazed porcelain tiles are in a 6" x 24" plank format
- Gorgeous realism—thanks to Clarity Digital Imaging, the color is rich and the detail is lavish
- Incredibly durable, it's freeze-thaw stable and literally goes anywhere—put it inside, outside, in the basement or on the deck, in residential or commercial installations
- Recycled content 40%
- Made in USA
- Two of the three colors (600 and 700) are proven best sellers—they're the two most popular colors in two of our most popular products (Pebble Hill hardwood and Heron Bay laminate)

We recommend that this product be installed with no less than a 3/16" grout joint.

Colors







600 Ancient rusty, red-toned brown



700 Fossil drenched dark brown

Petrified Hickory

Tile Sizes

Field Tile	Style
6" × 24"	CS65K
Technical	
Wear Rating Group	3* & 4
Break Strength	400 lbs.
Water Absorption	0.5%
COF (Wet)	>0.60
*color 700 only	

This tile features random variations of shade and texture within each carton. To insure optimum appearance, it is imperative that tiles from various cartons be continually blended during installation. Placement of tiles should be decided on before beginning installation.

*OSHA (Occupational Safety and Health Administration) has established a recognized industry standard of 0.5 (wet and dry) for slip-resistant surfaces. The Americans with Disabilities Act (ADA) recommends, but does not require, "a Static Coefficient of Friction of 0.60 for accessible routes and 0.80 for ramps." ADA does not specifically state that 0.60 is both a dry and a wet requirement. It is important to note that any tile or other hard surface flooring can become slippery when wet or improperly maintained. Products installed in an exterior application must comply with applicable ANSI 108 series of the "American National Standard Specifications for the Installation of Ceramic Tile" and comply with TCA installation methods applicable to installation conditions..



Approved Usage





