Shaw®
Tile & Stone™

CLASSICO
porcelain tile
shawfloors.com

100 Ivory

150 Light Grey

200 Beige

Shaw Tile & Stone™

CLASSICO
porcelain tile

Features

- Vein Cut Travertine Visual in a floor wall combination in three classic colors
- Features several rectangular shapes for a modern look
- Porcelain floor tile/Ceramic wall tile
- Made in Turkey

Colors

100 Ivory

150 Light Grey

200 Beige

10″ x 16″ wall **CS72F**

100 Ivory

150 Light Grey

200 Beige

Accents

12″ x 12″ x 2″ Mosaic **CS74F**

100 Ivory

150 Light Grey

200 Beige

2″ x 10″ Listello **CS73F**

100 Ivory

200 Beige

Specifications

Field Tile	**Style**
13x13	CS69F
18x18	CS70F
12x24	CS71F
10x16 wall*	CS72F
Trim	
Bullnose	CS75F
Wall Bullnose*	CS76F
Accent	
Mosaic	CS74F
Listello 2x10*	CS73F
Technical	
Wear Rating	4
Break Strength	302
Water Absorption	0.35
DCOF	0.55
Shading & TextureV2	Moderate

* Ceramic Body

This tile features random variations of shade and texture within each carton. To insure optimum appearance, it is imperative that tiles from various cartons be continually blended during installation. Placement of tiles should be decided on before beginning installation.

*OSHA (Occupational Safety and Health Administration) has established a recognized industry standard of 0.5 (wet and dry) for slip-resistant surfaces. The Americans with Disabilities Act (ADA) recommends, but does not require, "a Static Coefficient of Friction of 0.60 for accessible routes and 0.80 for ramps." ADA does not specifically state that 0.60 is both a dry and a wet requirement. It is important to note that any tile or other hard surface flooring can become slippery when wet or improperly maintained. Products installed in an exterior application must comply with applicable ANSI 108 series of the "American National Standard Specifications for the Installation of Ceramic Tile" and comply with TCA installation methods applicable to installation conditions..

Approved Usage

F FLOORS
W WALLS
E EXTERIOR

CERTIFIED PORCELAIN TILE™
0.5% or less water absorption