

Color shown is 700 Chai





Shaw Industries, Inc. PO Drawer 2128, Mail Drop 02601 Dalton, GA 30722-2128 1-800-441-7429

Buxy

Features

- On-trend limestone visual in three soft, light neutrals with low color variation and marbled veining
- Floor/wall combo including a complete deco package with listello and wall accent
- Great value in a porcelain tile

Accents

Listellos



100 Latte



101 Hazelnut



700 Chai

Wall Decos



100 Latte



101 Hazelnut



700 Chai

Mosaics



100 Latte



101 Hazelnut



700 Chai

Tile Sizes

Field Tile

13" × 13"	CS80E
18" × 18"	CS81E
10" x 13 " Wall Tile	CS82E

Trim

3"×	13" Bullnose	CS84E
3"×	10" Wall Bullnose	CS88E

Accent

13" × 13" Mosaic	CS85E
10" x 13" Wall Deco	CS86E
3.2" × 10" Wall Listello	CS87E

Technical

Wear Rating Group	4
Break Strength	323/437 lbs.
Water Absorption	0.25%
COF (Wet)	.64

This tile features random variations of shade and texture within each carton. To insure optimum appearance, it is imperative that tiles from various cartons be continually blended during installation. Placement of tiles should be decided on before beginning installation.

*OSHA (Occupational Safety and Health Administration) has established a recognized industry standard of 0.5 (wet and dry) for slip-resistant surfaces. The Americans with Disabilities Act (ADA) recommends, but does not require, "a Static Coefficient of Friction of 0.60 for accessible routes and 0.80 for ramps." ADA does not specifically state that 0.60 is both a dry and a wet requirement. It is important to note that any tile or other hard surface flooring can become slippery when wet or improperly maintained. Products installed in an exterior application must comply with applicable ANSI 108 series of the "American National Standard Specifications for the Installation of Porcelain tile" and comply with TCA installation methods applicable to installation conditions...

Approved Usage



