



Colors shown 200 Limestone and 600 Bronze



Tile & Stone™
shawfloors.com

Capri | *porcelain tile*



Tile & Stone™

shawfloors.com

Shaw Industries, Inc.
PO Drawer 2128, Mail Drop 02601
Dalton, GA 30722-2128
1-800-441-7429

Capri

Features

This antique travertine visual with chiseled edges and slightly patina surface emulates a time worn stone from classical periods of European architecture. Deep, rich colors give Capri a classic beauty and enduring quality. Traditional field tile sizes paired with simple mosaics make this an excellent series for living areas, kitchen floors and bathrooms.

- Antique travertine visual
- Patina surface gives a time worn look enhanced by the subtle chiseled edges
- Made in Brazil
- PTCA Certified Porcelain

Colors



200 Limestone



300 Flora




600 Bronze




700 Walnut

Accents


MOSAIC



200 Limestone



300 Flora



600 Bronze



700 Walnut


SUBWAY MOSAIC




200 Limestone



300 Flora



600 Bronze



700 Walnut

Tile Sizes

Field Tile	Style
12x12	CS77F
18x18	CS78F

Trim

Bullnose	CS79F
----------	-------

Accent

Mosaic	CS80F
Subway Mosaic	CS81F

Technical

Wear Rating Group	4 and 3*
Break Strength	250 lbs.
Water Absorption	< .5%
COF (Wet)	.52

*Wear rating 3, color 300, 600, & 700

This tile features random variations of shade and texture within each carton. To insure optimum appearance, it is imperative that tiles from various cartons be continually blended during installation. Placement of tiles should be decided on before beginning installation.

*OSHA (Occupational Safety and Health Administration) has established a recognized industry standard of 0.5 (wet and dry) for slip-resistant surfaces. The Americans with Disabilities Act (ADA) recommends, but does not require, "a Static Coefficient of Friction of 0.60 for accessible routes and 0.80 for ramps." ADA does not specifically state that 0.60 is both a dry and a wet requirement. It is important to note that any tile or other hard surface flooring can become slippery when wet or improperly maintained. Products installed in an exterior application must comply with applicable ANSI 108 series of the "American National Standard Specifications for the Installation of Ceramic Tile" and comply with TCA installation methods applicable to installation conditions.



Approved Usage

