

Color shown is 200 Beige and Mosaic color 200.





# Tile & Stone™

Shaw Industries, Inc. PO Drawer 2128, Mail Drop 02601 Dalton, GA 30722-2128 1-800-441-7429

# Summerwind

### **Features**

- Intriguing variations in color give this stunning glazed porcelain tile an intricate surface texture reminiscent of natural crystalline marble.
- Porcelain floor tile Ceramic wall tile
- Three colors available in 13" and 18" field tiles

## Colors







100 Ivory

200 Beige

750 Taupe

### Accent









## Tile Sizes

Field Tile	Style
18" × 18"	CS87J
13" × 13"	CS86J
10" x 16" Wall Tile*	CS83J

#### Trim

3" x 13" Bullnose **CS89**] 3" × 10" Wall Bullnose\* **CS88**]

#### Accent

10" x 16" Wall Deco\* **CS82I**  $13" \times 13" \times 2" \times 2"$  Mosaic **CS851** 2.2" × 10" Wall Listello\* **CS84**J

#### **Technical**

Wear Rating Group 332-407 lbs. Break Strength 0.13% Water Absorption COF (Wet) .63 \*ceramic body

This tile features random variations of shade and texture within each carton. To insure optimum appearance, it is imperative that tiles from various cartons be continually blended during installation. Placement of tiles should be decided on before beginning installation.

\*Ceramic Tiles \*\*OSHA (Occupational Safety and Health Administration) has established a recognized industry standard of 0.5 (wet and dry) for slip-resistant surfaces. The Americans with Disabilities Act (ADA) recommends, but does not require, "a Static Coefficient of Friction of 0.60 for accessible routes and 0.80 for ramps." ADA does not specifically state that 0.60 is both a dry and a wet requirement. It is important to note that any tile or other hard surface flooring can become slippery when wet or improperly maintained. Products installed in an exterior application must comply with applicable ANSI 108 series of the "American National Standard Specifications for the Installation of Ceramic Tile" and comply with TCA installation methods applicable to installation



# Approved Usage





