

Valhalla | porcelain tile

shawfloors.com



Valhalla

Features

- This complete package features beautiful undulting travertine visuals found in todays most popular sizes and colors. With the wall and field tile options, the possiblities are endless
- Porcelain floor tile Ceramic wall tile
- Three colors available in 13" and 18" field tiles

Colors







100 Ivory

200 Beige

700 Noce

Accent









CS93| Mosaic

Tile Sizes

Field Tile

13" × 13"	CS94J
18" × 18"	CS95J
10" x 16" Wall Tile*	CS91J

Trim

3"×	13" Bullnose	CS97J
3"×	10" Wall Bullnose*	CS96

Accent

10" × 16" Wall Deco*	CS90J
$13" \times 13" \times 2" \times 2"$ Mosaic	CS93J
3" × 10" Wall Listello*	CS92J

Technical

Wear Rating Group	3 & 4**
Break Strength	304/412 lbs.
Water Absorption	.16%
COF (Wet)	0.6 tile
*ceramic body	

** color 700 — 3

This tile features random variations of shade and texture within each carton. To insure optimum appearance, it is imperative that tiles from various cartons be continually blended during installation. Placement of tiles should be decided on before beginning installation.

*Ceramic Tiles **OSHA (Occupational Safety and Health Administration) has established a recognized industry standard of 0.5 (wet and dry) for slip-resistant surfaces. The Americans with Disabilities Act (ADA) recommends, but does not require, "a Static Coefficient of Friction of 0.60 for accessible routes and 0.80 for ramps." ADA does not specifically state that 0.60 is both a dry and a wet requirement. It is important to note that any tile or other hard surface flooring can become slippery when wet or improperly maintained. Products installed in an exterior application must comply with applicable ANSI 108 series of the "American National Standard Specifications for the Installation of Ceramic Tile" and comply with TCA installation methods applicable to installation conditions.



Approved Usage





