



Color shown is 900 Carbon

 **Shaw** Tile & Stone™
shawfloors.com

Lava | *porcelain tile*



Tile & Stone™

shawfloors.com

Shaw Industries, Inc.
PO Drawer 2128, Mail Drop 02601
Dalton, GA 30722-2128
1-800-441-7429

Lava

Features

Lava has a bold feel—resembling stained concrete—coupled with creative color depth.

- Colors are intense, giving an organic weathered appearance to the surface—these are the burning shades and dark smoky tones produced by volcanic eruption. Meticulously layered, each glaze creates an inviting, very subtle depth.
- A final glaze application produces a delicate crystallized effect, adding movement to the surface.
- Lava is perfectly suited for those who love the look of metallic tiles but don't want the flamboyant appearance often found in these popular styles.


Colors



500 Ash



600 Magma



900 Carbon

Accents

Listellos



500 Ash




900 Carbon

Mosaics



500 Ash



600 Magma



900 Carbon

Tile Sizes

Field Tile	Style
13" x 13"	CS95C
20" x 20"	CS96C

Trim	
3" x 13" Bullnose	CS19D

Accent	
1.5" x 13" Listello	CS41D
13" x 13" x 1" Mosaic	CS20D

Technical	
Wear Rating Group	3
Break Strength	390
Water Absorption	<.5%
COF (Wet)	.50

This tile features random variations of shade and texture within each carton. To insure optimum appearance, it is imperative that tiles from various cartons be continually blended during installation. Placement of tiles should be decided on before beginning installation.

*OSHA (Occupational Safety and Health Administration) has established a recognized industry standard of 0.5 (wet and dry) for slip-resistant surfaces. The Americans with Disabilities Act (ADA) recommends, but does not require, "a Static Coefficient of Friction of 0.60 for accessible routes and 0.80 for ramps." ADA does not specifically state that 0.60 is both a dry and a wet requirement. It is important to note that any tile or other hard surface flooring can become slippery when wet or improperly maintained. Products installed in an exterior application must comply with applicable ANSI 108 series of the "American National Standard Specifications for the Installation of Ceramic Tile" and comply with TCA installation methods applicable to installation conditions.

Approved Usage

