

Rustic Expressions Pine | laminate



141 Illinois Pine



500 Jackson Pine



740 dakota Pine

Color shown is 740 Dakota Pine

shawfloors.com

Rustic Expressions Pine | laminate

Features

Enjoy the rustic charm of times past with this wide plank pine collection. Rustic Expressions Pine features TouchableTexture™ — a truly natural surface texture you can see and feel. Offered in three rich pine colorations, this outstanding product is sure to enhance any room with rustic simplicity. Simple to install, simple to maintain, Rustic Expressions Pine is a perfect flooring choice for today's busy lifestyles.

- Featuring Shaw's single action LocNPlace® installation system for unsurpassed speed of installation
- 25-year limited residential wear, stain, fade and moisture resistance warranty
- OptiCore™ — Shaw's ultra dense core board that's strong, stable and moisture resistant.

Suggested Underlayment | Maintenance

- **SLFOA – Foam**
100 sq. ft. rolls/48" wide
(polyethylene foam)
48" x 25" x 5/64" T
Rls/plt - 120
- **SL2NI – 2 in 1 Foam**
100 sq. ft. rolls/40" wide
(polyethylene foam)
40" x 30" x 5/64" T
12 rolls per box / 12 boxes per pallet
- **SLPLF – Poly Film**
120 sq. ft. roll / 6mil
12 rolls per box / 12 boxes per pallet
- **SLSFP – Sofsound II**
200 sq. ft. roll / 6mil
72' x 33.33" x 1/8" T
30 rolls per pallet / 648 rolls per truck
- **SLSSU – SilentStep Ultra**
100 sq. ft. rolls
40" x 360" x 3/32" T
7 rolls per box / 12 boxes per pallet
- **SL100 – Selitac**
100 sq. ft. rolls
425'L x 48"W x 5/64
48 pallets per truck
- **SL101 – Selitac Tape**
30 rolls per box
1.96"W x 164'L
- **SHCLN – Hard Surface Cleaner**
32oz. Bottle
12 per Box / 55 cases per pallet

Specifications

Style	SL041
Thickness	5/16" (8mm)
Length	47 ⁹ / ₁₆ "
Width	11 ¹³ / ₃₂ "
Texture	Registered Embossed
Edge Description	Square
Sq. Ft. per carton	30.17
Sq. Ft. per pallet	1,357.65



This Shaw Laminate is warranted not to stain or wear through, will not fade as a result of direct sunlight or artificial light and will resist water damage under normal use conditions for 25 years.



This Shaw Laminate is warranted not to stain or wear through, will not fade as a result of direct sunlight or artificial light and will resist water damage under normal commercial use conditions for 5 years.



This Shaw laminate is constructed using LocNPlace® technology, Shaw's single action glueless locking system which greatly enhances the speed and ease of installation while improving seam integrity.



This Shaw laminate features Touchable Texture™ enhanced embossing technology.



This product is made with OptiCore™ - Shaw's laminate coreboard that's strong, stable and moisture resistant.



This product Greenguard certified for low chemical emissions



This Shaw product can be installed above, on or below ground level.



This Shaw product is Made in the U.S.A.



SVTMD
T-Molding



SVQTR
Quarter Molding



SVSTR
Stairnosing



SVMPR
Threshold / End Molding /
Carpet Reducer



SVWLB
Wall Base



SVTRK
Molding Track