

Landscapes | *laminates*



168 Holbrook Maple



258 Eastlake Hickory



291 Nightsong Hickory



619 Seneca Maple



623 Landmark Hickory



867 Catella Maple

Features

Eastlake Hickory and Catella Maple

These two smooth-surface styles offer popular 8"-wide planks in the lustrous look of maple and hickory. Soft, subtle graining, characteristic wormholes, and color variations give an aged, gracefully worn finish.

Nightsong Hickory and Landmark Hickory

Trendy 8" planks are a sought-after visual, giving these laminate styles added appeal. Both share the look of reclaimed hickory, with marks of age and wear and antique shading on the edges.

Seneca Maple and Holbrook Maple

These two styles come in 8" planks that suggest the appearance of two strips within each plank. There's high variation among the planks and a painterly, watercolor effect that creates a sophisticated visual.

Suggested Underlayment | Maintenance

- **SLFOA – Foam**
100 sq. ft. rolls/48" wide
(polyethylene foam)
48" x 25" x 5/64" T
Rls/plt - 120
- **SL2NI – 2 in I Foam**
100 sq. ft. rolls/40" wide
(polyethylene foam)
40" x 30" x 5/64" T
12 rolls per box / 12 boxes per pallet
- **SLPLF – Poly Film**
120 sq. ft. roll / 6mil
12 rolls per box / 12 boxes per pallet
- **SLSFP – Sofsound II**
200 sq. ft. roll / 6mil
72' x 33.33" x 1/8" T
30 rolls per pallet / 648 rolls per truck
- **SLSSU – SilentStep Ultra**
100 sq. ft. rolls
40" x 360" x 3/32" T
7 rolls per box / 12 boxes per pallet
- **SL100 – Selitac**
100 sq. ft. per box
425'L x 48"W x 5/64
48 pallets per truck
- **SL101 – Selitac Tape**
30 rolls per box
1.96"W x 164'L
- **SHCLN – Hard Surface Cleaner**
32oz. Bottle
12 per Box / 55 cases per pallet

Specifications

Style	Landscapes SL296	Landscapes Plus SL305
Thickness	1/4" (7mm)	5/16" (8mm)
Length	47 ⁹ / ₁₆ "	47 ⁹ / ₁₆ "
Width	8"	8"
Texture	Enhanced	Enhanced
Edge Description	Square	Square
Sq. Ft. per carton	26.40	21.12
Sq. Ft. per pallet	1,584.00	1,267.00



This Shaw Laminate is warranted not to stain or wear through, will not fade as a result of direct sunlight or artificial light and will resist water damage under normal use conditions for 25 years.



This Shaw Laminate is warranted not to stain or wear through, will not fade as a result of direct sunlight or artificial light and will resist water damage under normal commercial use conditions for 5 years.



This Shaw laminate is constructed using VersaLock®AG™, Shaw's patented locking technology that reliably secures the flooring panels on all four sides without adhesive.



This product GreenGuard certified for low chemical emissions



This Shaw product can be installed above, on or below ground level.



This Shaw product is Made in the U.S.A.



SVTMD
T-Molding



SVQTR
Quarter Molding



SVSTR
Stair nosing



SVMPR
Threshold / End Molding /
Carpet Reducer



SVWLB
Wall Base



SVTRK
Molding Track