

931 Horseman





Shaw Industries, Inc. PO Drawer 2128, Mail Drop 02601 Dalton, GA 30722-2128 1-800-441-7429

Sleepy Hollow Oak

Specifications

Style **SW180** Thickness 3/8" (10mm) Width 31/4" and 5" **Species** Oak 1802 Janka Hardness Rating Edge Description Microbeveled End Description Microbeveled

*Cartons may include random lengths



This Shaw Epic hardwood is warranted that the face surface will not peel off or wear through for as long as you own your home.



This product features ScufResist™ PLATINUM - Shaw's extremely wear resistant UV cured polyurethane finish with Aluminum Oxide designed to help resist household scuffing on hardwood floors.



This Shaw Epic® hardwood is made with Shaw's EnviroCore® and provides unsurpassed structural integrity, impact resistance and dimensional stability.



This Shaw hardwood product meets GREENGUARD indoor air quality requirements and is GREENGUARD Children

& Schools Certified.



This Shaw hardwood is approved for installation over water type radiant heated subfloors when installed as a glued or floating floor. (Oak, Ash, Hickory or Walnut veneer species only.)



This Shaw Epic[®] hardwood is Cradle to Cradle^{CM} Silver



This hardwood is rated Moderate with distinguishable color and character variation within each box. It is imperative that hardwood planks from various cartons be continually blended during installation to insure optimum appearance.



This Shaw product is made in the USA.

Features

Artisans scrape every plank of Sleepy Hollow Oak by hand to give it a time-worn texture. Plus 31/4" and 5" widths are packaged together to create a random-width "designer" floor.

- This product carries a limited now & forever Lifetime Wear Warranty
- This product features ScufResist™ PLATINUM Shaw's extremely wear resistant UV cured polyurethane finish with Aluminum Oxide designed to help resist household scuffing on hardwood floors
- This Shaw product can be installed above, on or below ground level
- This hardwood is approved for installation over water type radiant heated subfloors when installed as a glued or floating floor
- Installation methods: nail, staple, glue, float
- Made with Pride by Shaw in the USA

Color



798 Ichabod



931 Horseman